

Amendments to the claims:

RECEIVED
CENTRAL EXAMINER
SEP 27 2006

1. (currently amended) A quick-action chuck, ~~in particular for a power tool,~~
comprising:

~~having~~ an actuating element (20); and

~~having~~ a control device which includes at least one means (12, 22, 36, 42, 50) for controlling at least one locking device (10) that serves to absorb a chucking reinforcement force, ~~characterized in that~~ wherein via the locking device (10) that is controllable by the control device, a positive-engagement connection can be brought about for absorbing the chucking reinforcement force, wherein the at least one locking device (10) is rotatable relative to a base body (32) for bringing about the positive-engagement connection, wherein chucking jaws (26) are guided in the base body (32), wherein said base body (32) has at least one slide face (64) on which the at least one locking device (10) is axially displaceable, wherein said base body has a set of teeth (48) in which the at least one locking device (10) engages in a locking position, and wherein as a result of meshing with the set of teeth (48), the at least one locking device (10) is axially fixed on the base body (32).

2. (canceled)

3. (currently amended) The quick-action chuck of claim 1, ~~characterized in that~~ wherein the control device is a locking spring (22).

4. (currently amended) The quick-action chuck of claim 1, ~~characterized in that~~ wherein ~~the~~ a tool (34) can be chucked indirectly via a spring means (12) that is actuatable by the actuating element (20).

5. (currently amended) The quick-action chuck of claim 1, ~~characterized in that~~ wherein the actuating element (20) can be operatively uncoupled from the locking device (10) over at least one actuation region.

6. (currently amended) The quick-action chuck of claim 1, ~~characterized in that~~ wherein the actuating element (20) is rotatably supported for chucking the tool (34).

7. (currently amended) The quick-action chuck of claim 1, ~~characterized in that~~ wherein the actuating element (20) is supported displaceably in the axial direction.

8. (canceled)

9. (currently amended) The quick-action chuck of claim ~~3~~ 2, ~~characterized in that~~ wherein the actuating element (20) can be coupled to the base body (32) and uncoupled from it via the locking spring (22).

10. (currently amended) The quick-action chuck of claim ~~15~~ 9, characterized in that wherein the locking spring (22) has an essentially annular shape.

11. (currently amended) The quick-action chuck of claim ~~4~~ 4, characterized in that wherein the spring means (12), for chucking the tool (34), has an essentially annular shape.

12. (currently amended) The quick-action chuck of claim 11, characterized in that wherein the spring means (12) has at least two detent elements (14, 16), opposite one another on the circumference, for snapping into the actuating element (20).

13. (currently amended) The quick-action chuck of claim 1, characterized by further comprising at least one chucking jaw (26), which is loaded in an the axial direction in at least one operating position via a spring element (24).

14. (currently amended) A power tool having a quick-action chuck of claim ~~4~~, said quick-action chuck comprising:
an actuating element (20); and
a control device which includes at least one means (12, 22, 36, 42, 50) for controlling at least one locking device (10) that serves to absorb a chucking reinforcement force, wherein via the locking device (10) that is controllable by the

control device, a positive-engagement connection can be brought about for absorbing the chucking reinforcement force.

15. (new) A quick-action chuck, comprising:

an actuating element (20); and

a control device which includes at least one means (12, 22, 36, 42, 50) for controlling at least one locking device (10) that serves to absorb a chucking reinforcement force, wherein via the locking device (10) that is controllable by the control device, a positive-engagement connection can be brought about for absorbing the chucking reinforcement force, wherein the control device is a locking spring (22), and wherein the actuating element (20) can be coupled to the base body (32) and uncoupled from it via the locking spring (22).

16. (new) A quick-action chuck, comprising:

an actuating element (20); and

a control device which includes at least one means (12, 22, 36, 42, 50) for controlling at least one locking device (10) that serves to absorb a chucking reinforcement force, wherein via the locking device (10) that is controllable by the control device, a positive-engagement connection can be brought about for absorbing the chucking reinforcement force, wherein a tool (34) can be chucked indirectly via a spring means (12) that is actuatable by the actuating element (20), wherein the spring means (12), for chucking the tool (34), has an essentially annular shape, and wherein the spring means (12) has at least two detent

elements (14, 16), opposite one another on the circumference, for snapping into the actuating element (20).